


Matthias Simons - Daimler AG
Mihai Feier, Jakob Maus @ habermas@ti0D




(* Motivation



/* 4unnin ! C1 functions on 5C &ia chi# simulation

0* Cou#lin 6ith least-s7uares o#timi3ation



8* Conclusion



- number of online control parameters
: doubles every 6 years
- budget for online calibration
: does not
- increase degree of automation
- move calibration tasks from test rigs
to 5C and mathematical
optimization







source: representation of S* 1 Ilmann \$ ' M = %
>th Conference on D2 !, / - - ,







object & function












characteristics turne : into
MATBA ' 6orks#ace &variables
- rea: b; S-function
- ma; be mo: ifie: b; scri#t



MATBA ' DSimulink
S-function
%)"



:efault &alues for
characteristics from
H!C file as m scri#t,
mask for S-function
block an: similar
Simulink sni##ets



' ! 3




5 ! " ! j




	" !	'
Sil&er in :ebu mo:e	, (, * (> sec	-*8(
enerate: Sil&er mo:ule or MATBA ' DSimulink SFunction	, *0- sec	8-*) -
M!D(7 6ith TC(7,7, () - Mh3	/ (-* - - sec	/7-



!



!




2




(!



!



!







2#timization metho:s often re7uire
to ui:e search

!n ine control often im#lemente:
usin " co:e

A ra:ients of the oal function
are 3ero \$or un:efine: %



A no ui:ance

A o#timization terminates earl;
at local o#timum



+

!



Hij :oes not chan e much
 :urin the solution #rocess<
 comr'S'3\$uop hJan %"3M0nlu co:

